

EHST17/20/30D

For Ecodan Split System Air Source Heat Pumps

R32

FTC6 Cylinders

These split integrated cylinders offer a highly adaptable heating and hot water solution for retrofit and new build.

Designed specifically by Mitsubishi Electric to operate with the Ecodan split air source heat pump range. The cylinder provides market leading domestic hot water performance with faster heat up times through the use of plate heat exchanger technology. Easy installation, fast commissioning via an SD card and built in energy monitoring are some of the functions that are included.

Key Features:

- Fully integrated sleek modern design
- Market leading ErP domestic hot water efficiency
- Pre-plumbed and wired for faster installation
- Set up wizard for easy start up
- SD Card Commissioning
- All water connections to rear of unit
- 170, 200 and 300 litre options available
- Energy monitoring as standard
- Wi-Fi compatible for remote connection



ecodan[®]
Renewable Heating Technology

Model Name		EHST17D-VM2D	EHST20D-VM2D	EHST30D-VM6ED
	Nominal hot water volume (Litres)	170	200	300
Dimensions (mm)	Height (mm)	1400	1600	2050
	Width (mm)	595	595	595
	Depth (mm)	680	680	680
Casing	Munsell	6.2 Pb 9/0.9	6.2 Pb 9/0.9	6.2 Pb 9/0.9
	RAL Code	260 90 05	260 90 05	260 90 05
	Material	Pre- coated metal	Pre- coated metal	Pre- coated metal
	Weight empty/full (kg)	93 / 269	99 / 305	115 / 422
Refrigerant	Connection type refrigerant pipe (OD) (Liquid mm(in))	6.35 (1/4") Flared	6.35 (1/4") Flared	6.35 (1/4") Flared
	Gas mm(in)	12.7 (1/2") Flared	12.7 (1/2") Flared	12.7 (1/2") Flared
Water data	Connection type water (Primary) (mm)	28	28	28
	Connection type water (Domestic hot water) (mm)	22	22	22
	Flow rate (Primary circuit) Min*1/ Max *2 (L/Min)	5.0 / 25.8	5.0 / 36.9	5.0 / 36.9
	Cylinder material	Duplex 2304 stainless steel (EN10088)	Duplex 2304 stainless steel (EN10088)	Duplex 2304 stainless steel (EN10088)
	Primary expansion vessel (Volume) (L)	12	12	-
	Primary expansion vessel (Charge pressure) (Mpa)	0.1	0.1	-
Water safety devices (Primary circuit)	Control thermistor (°C)	1 ~ 80	1 ~ 80	1 ~ 80
	Pressure relief valve (Mpa)	0.3	0.3	0.3
	Flow sensor minimum (L/Min)	5	5	5
Water safety devices (DHW circuit)	Control thermistor (°C)	75	75	75
	Temperature and pressure relief valve	1.0 Mpa (10 bar)	1.0 Mpa (10 bar)	1.0 Mpa (10 bar)
Electric data (Control Board)	Electrical supply (single phase)	220 - 240V 50Hz	220 - 240V 50H	220 - 240V 50H
	Current (Amps)	1.95	1.95	1.95
	Fuse rating (MCB) (Amps)	10	10	10
Electric data (Booster Heater)	Electrical load (kW)	2	2	2 + 4
	Current (Amps)	9	9	26
	Fuse rating (MCB) (Amps)	16	16	32
Noise	Sound power level (dBa)	41	41	41
Mechanical zones		DHW & 2 Heating Zones	DHW & 2 Heating Zones	DHW & 2 Heating Zones
ErP data (average climate)	Water heating energy efficiency			
	SUZ-SWM40VA (η _{wh})	148%	159%	-
	SUZ-SWM60VA (η _{wh})	144%	148%	-
	SUZ-SWM80VA (η _{wh})	144%	148%	127%
	PUD-SHWM80VAA	136%	148%	121%
	PUD-SHWM100VAA	-	148%	121%
	PUD-SHWM120VAA	-	148%	121%
	PUD-SHWM140VAA	-	145%	121%
	Declared load profile	L	L	XL

*1 If the water flow rate is less than the minimum a flow error will be activated

*2 If the water flow rate range exceeds maximum, flow speed will be greater than 1.5m/s which could corrode the pipes




Telephone: (01) 419 8800


IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

©Mitsubishi Electric Europe. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.





DHW tank capacity	170L	200L	300L
H (mm)	1400	1600	2050



Letter	Pipe description	Connection size/type
A	DHW outlet connection	22 mm/Compression
B	Cold water inlet connection	22 mm/Compression
C	Space heating RETURN connection	28 mm/Compression
D	Space heating FLOW connection	28 mm/Compression
E	Refrigerant (GAS)	12.7 mm/Flare
F	Refrigerant (LIQUID)	6.35 mm/Flare



Telephone: (01) 419 8800

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

©Mitsubishi Electric Europe. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.

